

JOB ADDRESS \_\_\_\_\_

WIND SPEED \_\_\_\_\_

EXPOSURE \_\_\_\_\_

BUILDING HEIGHT \_\_\_\_\_ STORIES \_\_\_\_\_



**This form may be used ONLY for Installation or Replacement of  
DOORS, WINDOWS, and SHUTTERS  
In Multi-Family Buildings up to 3-Stories and  $\leq 30'$  high!**

Tables 1609.6.B & C

\*COMPONENTS AND CLADDING WORST CASE DESIGN PRESSURE [PSF]

- 130 EXPOSURE B ZONE 4 = + 30.4 - 33.0
- 130 EXPOSURE B ZONE 5\* = + 30.4 - 40.7
  
- 140 EXPOSURE B ZONE 4 = + 35.3 - 38.2
- 140 EXPOSURE B ZONE 5\* = + 35.3 - 47.2
  
- 140 EXPOSURE C ZONE 4 = + 49.42 - 53.48
- 140 EXPOSURE C ZONE 5\* = + 49.42 - 66.08

\*End-Zone 5 can never be LESS than 3 ft

**WINDOWS**

REMOVE EXISTING WINDOWS. SECURE EXISTING BUCKS. INSTALL NEW WINDOW(S) PER PRODUCT APPROVAL. HAVE PRODUCT APPROVAL AVAILABLE AT TIME OF INSPECTION.

**NOTE: Glazing in hazardous locations must comply with Section 2405**

**DOORS**

REMOVE EXISTING EXTERIOR DOOR, SECURE EXISTING BUCKS. INSTALL NEW DOOR(S) PER PRODUCT APPROVAL & HAVE PRODUCT APPROVAL AVAILABLE AT TIME OF INSPECTION.

**NOTE: Glazing in hazardous locations must comply with Section 2405**

**SHUTTERS**

INSTALL SHUTTERS PER SHUTTER ENGINEERING. HAVE PRODUCT APPROVAL AVAILABLE AT TIME OF INSPECTION.

**IMPORTANT NOTICES:**

- Per Florida Building Code Existing - Shutter or impact-resistant glass is required for ALL replacement windows and doors with glazed openings.
- Emergency Escape & Rescue must be provided / maintained per Section 1025